

Main applications

Bimini top
Cockpit enclosure



UPF 50+: 100% UV protection

Unrivalled performance
to protect the crew

Major advantages

- Extreme resistance to UV & mould
- 100% UVB protection
- Easy cleaning
- Waterproof
- Long lasting colours

Other applications

- Sprayhoods
- Shade sails
- Retractable roofs

Technical specifications

Weight	430 g/m ² - EN ISO 2286-2
Standard format length	30 lm in 260 cm/50 lm in 150 cm
Tensile strength (warp/weft)	120/120 daN/ 5 cm - EN ISO 1421
Tear strength (warp/weft)	6/7 daN - DIN 53.363
Colour light fastness	> 4/5 (1000 hours) - ISO 105-B02
UV filtration	UPF 50+ - NF EN 13758-1+A1
Mould resistance	Degree 0, excellent - EN ISO 846-A
Warranty	5 years
MOQ	2000 lm
Maximum delivery time	4 working weeks
Provided services	Special colour
Accessories	Stamoid Edge Serge Ferrari cleaner Lyb-2 Silcord


The technical data above are averaged values
with a +/- 5% tolerance.

**Smart Coating
Technology**


Serge Ferrari Stamoid

Top


15 colours & references




Snow White F3933-10309




White F3933-03244




Cream F3933-10204




Ivory F3933-10081




Sand F3933-01897




Desert F3933-20217




Taupe F3933-20165




Pearl grey F3933-10001




Royal blue F3933-04997




Navy F3933-10235




Cloud grey F3933-20218




Evergreen F3933-20031



Bordeaux F3933-20042



Charcoal F3933-20166



Black F3933-00002